



ELECTRICAL SPEC.

Detection System	Absolute 絕對值型
Output Code 輸出碼值	Gray Code
Standard Number of Pulse Per Revolution 解析	256
Electronics 電路特性	NPN Voltage 電壓型, NPN Open Collector 電流型
Power Supply 供應電源	DC 10~26V, DC 5V fixed
Current Consumption 消耗電流	≤ 70 mA
Logic 邏輯	Negative Logic (H=0, L=1) 負理論輸出
Max. Response 最大響應頻率	10K Hz

MECHANICAL SPEC.

Shaft Diameter 軸徑	6 mm
Shaft Loading 軸荷重	Axial 軸向: 1 Kg, Radial 徑向: 2 Kg
Max. Speed 最大機械容許速度	3,000 rpm
Vibration Resistance	Endurance 55 Hz double amplitude 1.5 mm / 2 hours in X, Y and Z directions
Shock Resistance	Endurance 500 m / S ² (50g) 3 times each in X, Y, Z direction
Cable 電線	Ø4.5, 50 cm long, vinyl shielded
Weight 重量	≤ 200g

ENVIRONMENTAL SPEC.

Operating Temp. / Humidity 操作溫度/濕度	0°C ~ 60°C, RH 35% ~ 90% (No Condensation)
Storage Temp. 儲存溫度	-20°C ~ 80°C
Protection 保護等級	IP50: Dust Proof

ORDERING INFORMATION

A2	Output Code 輸出信號	Pulse per Revolution 解析	Electronics 電路特性	Supply Voltage 供應電源
	G: Gray Code	256 P/R	BLANK: NPN Voltage C: NPN Open-Collector	Blank: 10~26 Vdc 5V: 5 Vdc fixed

ELECTRICAL CONNECTION

Wire Color (cable output)	256 PPR
Red	+V
Black	0V
Blue	bit 1 (2 ⁰)
Green	bit 2 (2 ¹)
Yellow	bit 3 (2 ²)
Violet	bit 4 (2 ³)
Orange	bit 5 (2 ⁴)
Brown	bit 6 (2 ⁵)
White	bit 7 (2 ⁶)
Gray	bit 8 (2 ⁷)
Shield	—